

Face Construction	IMPERIAL	METRIC
Construction	Woven Textured Loop	
Woven Pile Weight	40 oz/sq yd	1356 g/sq m
Rows Per Inch	8.8 rows/inch	34.6 rows/10 cm
Pitch	135 5.0 / inch	19.7 rows/10 cm
Finished Pile Height	0.237 inch	6.0 mm
	0.079 inch	2.0 mm
Total Finished Weight	66.10 oz/sq yd	2241 g/sq m
Kilotex	16.6	
Fiber System	TDX nylon	
Dye Method	Solution Dyed	
Pattern Repeat	0.40 " W x 0.45 " L	10.16 mm W x 11.43 mm L
Soil Protection	ENSURE	
Primary Backing	Woven Polypropylene	
Backing Construction	Crossweave®	
Width	12 feet	366 cm

### Color Line

01187 Topaz	01181 Kiwi	01194 Terrain
01184 Folkstone	01189 Laser	01195 Morel
01183 Earth	01190 Pulse	01196 Calcite
01188 Silicon	01191 Sand Flats	01197 Pewter
01185 Phantom	01192 Raku	
01186 Ebony	01193 Corn Row	

### Product Testing/Information

IAQ Results	CRI Green Label Plus Registration Number GLP3115. (Low VOC emitter.)	
Surface Flammability	Methenamine Pill	Meets CAN/CGSB-4.129-93/DOC FF 1-70
	Flooring Radiant Panel	ASTM E-648 Class 1 (Direct Gluedown)
	Smoke Density	ASTM E-662 Less than 450
	Steiner Tunnel	ULC S102.2 Less than 300FS, 500SD

The product, represented by averages of testing from random samplings of production lots, meets or exceeds the above Test Results.

### Warranties

5 Year Limited Colourfastness (Atmospheric Fumes)
10 Year Limited Colourfastness (Light)
15 Year Limited Abrasive Wear
Lifetime Limited Anti-Static (Less than 3.5 kv)
Lifetime No Zipper or Edge Ravel

### Product Notes

All specifications are subject to normal manufacturing tolerances.  
 Dyelots may vary from samples.  
 The use of chair pads under roller caster chairs may be required in order to maintain full limited warranty coverage. Please refer to the applicable limited warranty verbiage for specific requirements. In all cases, chair pads are recommended for optimum textural performance. Absent the use of chair pads, more intensive maintenance will be required for areas in direct contact with chair caster traffic, and some degree of appearance change is to be expected.  
 Tandus Flooring reserves the right to change specifications and construction materials without notice due to raw material shortages or technological improvements, contact your representative for confirmation.

### Installation and Maintenance

Carpet is a textile fabric, subject to stretch and/or shrinkage. An acceptable pattern match is achievable, however, a perfect pattern match cannot be guaranteed.  
 To achieve best results, more time should be allowed to install patterned carpet. This styles has a definite pattern and must be installed according to pattern match procedures as outlined in Tandus Flooring installation specifications, available from your Tandus Flooring Representative.  
 Manufacturing tolerances on Tandus Flooring carpets are:  
 Bow - 3/4" per 12' width  
 Skew - 1" per 12' width  
 Edge Straightness - +/- 1/2" variation  
 Pattern Elongation - 1 1/4" per 12' length  
 For best side match and seam appearances, it is recommended to run seams perpendicular to external light sources.  
 Proper maintenance is critical to the long term performance of any carpet and should be written into the specification of a project.  
 Recommendations are available from your Tandus Flooring Representative.

See limited warranty for details. Limited warranty and maintenance information may be accessed at [www.tandus.com/limitedwarranty](http://www.tandus.com/limitedwarranty) and [www.tandus.com/maintenance](http://www.tandus.com/maintenance) or by dialing 800-248-2878.